

Air Top 2000



Advantages

- Integrated Diagnostic Capability
- Low Power Consumption
- Quiet Operation
- Variable Heat Output
- Integrated Control Unit
- Ceramic Glowpin Technology
- Unique 'Ferrotech' Burner Cartridge
- DefStan 59-41 Suppression Capability
- AVTUR Compatible

Technical Data

Rated Voltage		v	12 or 24
Rated Heat Output	Full Heat Mid-Range Reduced Heat	kW	2.0 Fully Variable 0.9
Fuel Consumption	Full Heat Reduced Heat	Ltrs/hr	0.24 0.12
Maximum Heated Airflow		m ³ /hr against 0.5mb	70
Fuel		Diesel*	
Noise Level	Full Heat Reduced Heat	dB(A)	56 48
Electrical Input	Start Up Full Heat Reduced Heat	W	80 22 Fully Variable 9
Dimensions of Heater	L x B x H	mm	490 x 180 x 185
Weight of Heater		kg	7

* Petrol Variant is available upon request—Please refer to Webasto Engineering for Technical Specification

Typical Applications

- Truck Cabin Heating
- Marine Installation
- Mobile Workshops
- Construction Equipment

Webasto Product UK Limited

Webasto House
White Rose Way
Doncaster Carr
South Yorkshire
United Kingdom
DN4 5JH

Phone : +44 (0) 1302 322232
Fax : +44 (0) 1302 322231
E-Mail: info@webastouk.com

Co Reg No : 2191825
VAT Reg No : 504 2738 67