

Air Top 5000



Advantages

- Integrated Diagnostic Capability
- Low Power Consumption
- Quiet Operation
- Variable Heat Output
- Integrated Control Unit
- Ceramic Glowpin Technology
- Unique 'Ferrotech' Burner Cartridge
- DefStan 59-41 Suppression capability
- AVTUR Compatible

Technical Data

Rated Voltage		v	12 or 24
Rated Heat Output	*Boost Full Heat Mid-Range Reduced Heat	kW	5.5 5.0 Fully Variable 1.5
Fuel Consumption	*Boost Full Heat Mid-Range Reduced Heat	Ltrs/hr	0.66 0.60 Variable 0.17
Airflow		m ³ /hr	218
Fuel		Diesel	
Noise Level	Full Heat Mid-Range Reduced Heat	dB(A)	61 Variable 41
Electrical Input	Start Up *Boost Full Heat Mid-Range Reduced Heat	W	80 90 80 Variable 15
Dimensions of Heater	L X B X H	mm	555 x 195 x 220
Weight of Heater		kg	11.7

Typical Applications

- Passenger Carrying Vehicles
- Marine Installations
- Ambulances
- Cargo Heating
- Shelter Heating

Webasto Product UK Limited

Webasto House
White Rose Way
Doncaster Carr
South Yorkshire
United Kingdom
DN4 5JH

Phone : +44 (0) 1302 322232
Fax : +44 (0) 1302 322231