

Defence Market
Air Heaters

HL90



Advantages

- Pressurised combustion chamber allows for exhaust lengths up to 5m
- The most compact heater in it's class
- Dual heat output increases the range of applications
- Thermostat sensing re-circulated air temperature
- Renowned burner technology with proven durability
- AVTUR Compatible
- High standard of RFI Suppression:

Technical Data

Rated Voltage		v	12	24
Rated Heat Output	Full Heat Reduced Heat	kW	9.0 6.5	
Fuel Consumption	Full Heat Reduced Heat	Ltrs/hr	1.2 0.86	
Heated Airflow	Full Heat Reduced Heat	m ³ /hr	280 195	310 215
Fuel			Diesel Only	
Electrical Input	Full Heat Reduced Heat	W	110 80	160 95
Dimensions of Heater	l x b x h	mm	650 x 300 x 375	
Weight of Heater	inc control unit & fuel pump	kg	21.60	

Typical Applications

- Large Combat Vehicles
- Shelter Heating
- Cargo Heating

Webasto Product UK Limited

Webasto House
White Rose Way
Doncaster Carr
South Yorkshire
United Kingdom
DN4 5JH

Phone : +44 (0) 1302 322232
Fax : +44 (0) 1302 322231
E-Mail: info@webastouk.com

Co Reg No : 2191825
VAT Reg No : 504 2738 67