

Thermo 90S



Advantages

- Pressurised combustion chamber allows for exhaust lengths up to 5m
- The most compact heater in it's class
- Variable heat output increases the range of applications
- Integrated diagnostic capability
- Unique "Ferrotec" Burner technology
- AVTUR Compatible
- Ceramic Glowpin Technology
- Application proven to :
DefStan 59-41 Class A—DRE 03
DefStan 59-41 for Ripple, Surges and Spikes

Technical Data

Rated Voltage		v	24
Rated Heat Output	Full Heat Control Range	kW	9.1 1.8—7.6
Fuel Consumption	Full Heat Control Range	Ltrs/hr	1.1 0.19—0.91
Power Consumption	Full Heat Control Range	W	90 37-83
Dimensions of Heater	l x b x h	mm	310 x 133 x 235
Weight of Heater	inc control unit & fuel pump	kg	5.5
Fuel Type			Diesel

Typical Applications

- Winterisation supporting engine, crew or auxiliary equipment heating

Webasto Product UK Limited

Webasto House
White Rose Way
Doncaster Carr
South Yorkshire
United Kingdom
DN4 5JH

Phone : +44 (0) 1302 322232
Fax : +44 (0) 1302 322231
E-Mail: info@webastouk.com

Co Reg No : 2191825
VAT Reg No : 504 2738 67